



Kassett-tüüpi siseosa

CC AERI



Mudel	ACP-09CCIFM25AERI	ACP-12CC35AERI/i3	ACP-18CC50AERI/i3
 Võimsus (W)	2638	3517	5280
Jahutamise temperatuurivahemik	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C
 Võimsus (W)	2931	4103	5422
Kütmise temperatuurivahemik	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C
Õhuvool (m³/h) - HI / MID / LOW	580 / 500 / 450	617 / 504 / 415	680 / 560 / 500
Jahutusvedelik	R32	R32	R32
Niiskuse eemaldamise võime (L/h)	1.0	1.2	1.8
Müra - Helirõhk (dB(A)) - KÕRGE / KESKINE / MADAL / TASA	38 / 33 / 29	41 / 37 / 34	44 / 42 / 41
Heli standardtingimustes (dB)	≤ 53	≤ 58	≤ 56
Seadme pakendi mõõdud (mm)	662 x 662 x 317	662 x 662 x 317	662 x 662 x 317
Paneeli pakendi mõõdud (mm)	715 x 715 x 123	715 x 715 x 123	715 x 715 x 123
Seadme mõõdud (mm)	570 x 570 x 260	570 x 570 x 260	570 x 570 x 260
Paneeli mõõdud (mm)	647 x 647 x 50	647 x 647 x 50	647 x 647 x 50
Paneeli bruto-/netokaal (kg)	4.5 / 2.5	4.5 / 2.5	4.5 / 2.5
Bruto-/netokaal (kg)	17.3 / 14.5	21.4 / 16.2	21.4 / 16.2
Ühendused Vedelfaasi toru läbimõõt	1/4"	1/4"	1/4"
Gaasilise faasi toru läbimõõt	3/8"	3/8"	1/2"
Ühendus-kaabel Välisseadme toide (mm²)	4 x 1.0	4 x 1.0	4 x 1.0
Toide	~220-240V/1/50Hz; Välisseade		

