

Põranda-lae sisesosad

CF AERI



R32
gas



Night
mode



1.0 W
Standby



Dust
filter



Self-cleaning



3D DC
Inverter



Error detection
and display



Heating at
a temp. of
-20 °C



Cooling at
a temp. of
-15 °C



The protective
cover of the
valve



I Feel
function



Last mode
memory



Timer



Louver
Position
Memory



Condensate
drain pump



Wired
control
device

Mudel

ACP-18CF50AERI/I3



Võimsus (W)

5280



Jahutamise temperatuurivahemik

-15 °C ≤ T ≤ 50 °C



Võimsus (W)

5570

Kütmise temperatuurivahemik

-20 °C ≤ T ≤ 30 °C

Ühendused

Öhuvool (m³/h) - HI / MID / LOW

958 / 839 / 723

Jahutusvedelik

R32

Niiskuse eemaldamise võime (L/h)

1.8

Müra - Helirõhk (dB(A)) - KÖRGE / KESKMINE / MADAL / TASA

43.5 / 41 / 36.5 / 24

Heli standardtingimustes (dB)

≤ 57

Pakendi mõõdud (mm)

1145 x 755 x 318

Seadme mõõdud (mm)

1068 x 675 x 235

Bruto-/netokaal (kg)

33.3 / 28

Ühendus- kaabel

Välisseadme toide (mm²)

4 x 1.0

Toide

~220-240V/1/50Hz;
Välisseade