

# Seina paigutusega siseosad AERI | AEVI | AEMI



Ionizer



Anti-corrosion protection - gold coating



Heating at temp. of -20°C



3D DC Inverter



Wi-Fi ready



Mono and multi compatibility



Operating range up to -20°C



Heating



Cooling



3D air flow



Wi-Fi ready



Mono and multi compatibility



Biofilter



Anti-corrosion protection - gold coating



3D DC Inverter








I Feel function



Automatic operating mode



Wi-Fi ready

Mudel	ACP-07CH21AEMI/I	ACP-09CH25AERI/I+ R32	ACP-12CH35AERI/I+ R32	ACP-18CH50AERI/I+ R32	ACP-12CH35AEVI/I2s R32
 Võimsus (W)	2052	2638	3517	5275	3517
 Võimsus (W)	2346	2931	3810	5568	3810
 Siseade					
Õhuvool (m³/h) - HI / MID / LOW	520 / 460 / 340	483 / 362 / 303	584 / 477 / 395	730 / 500 / 420	558 / 478 / 384
Jahutusvedelik	R32	R32	R32	R32	R32
Niiskuse eemaldamise võime (L/h)	1.0	1.0	1.2	1.8	1.2
Müra - Helirõhk (dB(A)) - KÕRGE / KESKINE / MADAL / TASA	40 / 30 / 26 / 21	42 / 35 / 25 / 21.5	42 / 35 / 25 / 22	43 / 38 / 33.5 / 28	37.5 / 32 / 30 / 24
Heli standardtingimustes (dB)	≤ 54	≤ 56	≤ 56	≤ 57	≤ 51
Pakendi mõõdud (mm)	870 x 270 x 360	875 x 285 x 375	875 x 285 x 375	1045 x 305 x 410	985 x 385 x 265
Seadme mõõdud (mm)	805 x 194 x 285	802 x 189 x 297	802 x 189 x 297	965 x 215 x 319	897 x 312 x 182
Bruto-/netokaal (kg)	9.7 / 7.5	11.1 / 8.6	11.1 / 8.6	14.2 / 10.9	14.2 / 10.5
 Ühendused					
Vedelfaasi toru läbimõõt	1/4"	1/4"	1/4"	1/4"	1/4"
Gaasilise faasi toru läbimõõt	3/8"	3/8"	3/8"	1/2"	3/8"
 Ühendus-kaabel					
Välisseadme toide (mm²)	4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0	5 x 1.5
Toide	~220-240V/1/50Hz; Välisseade				